APPENDIX B SIZING OF DISTRIBUTION TYPE TRANSFORMERS FOR FAMILY HOUSING UNITS

B-1. Application. Design factors apply only to aerial or pad-mounted compartmental distribution transformers supplying family housing units.

B-2. Distribution Transformers. Distribution transformers serving family housing areas will have the air conditioning or electric heating loads, whichever is larger, sized for 100 percent demand. The rest of the load will be sized in accordance with the demand factors of table B-l.

Table B-I. Demand Factors.

Number of units	Demand factor percent	Number of units	Demand factor percent	Number of units	Demand factor percent
	80.0	19	18.0	37	13.2
	60.0	20	17.5	38	13.0
	50.0	21	17.1	39	12.8
:	45.0	22	16.6	40	12.6
	40.0	23	16.1	41	12.4
	35.0	24	15.8	42	12.2
, 	32.0	25	15.6	43	12.0
	29.0	26	15.4	44	11.8
	27.0	27	15.2	45	11.6
0	25.0	28	15.0	46	11.4
1	24.0	29	14.8	47	11.2
2	23.0	30	14.6	48	11.0
3	22.0	31	14.4	49	10.8
4	21.0	32	14.2	50	10.6
5	20.0	33	14.0	51	10.4
6	19.4	34	13.8	52	10.2
7	18.7	35	13.6	53	10.1
8	18.3	36	13.4	54ª	10.0"

^a Same demand factor applies to all quarters over 54.